

# DOZER BLADES



JOHN DEERE

DB84 | DB96



# DOZER BLADES

DB84 | DB96



## Specifications

- Add a Worksite Pro™ Dozer Blade to turn your skid steer loader (SSL) or compact track loader (CTL) into a compact bulldozer.
- Nothing light-duty about these dozer blades. Their rugged design delivers maximum uptime to a wide variety of tasks — from stripping clay to finish grading.
- Quik-Tatch™-mounted blade comes standard equipped with reversible cutting edge and skid shoes for long-term durability.
- Power-angle-tilt lets you make blade adjustments on the go, for increased versatility and maximum productivity.
- Like all Worksite Pro™ attachments, these dozer blades are optimized to work with John Deere skid steers loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They are also compatible with many competitive models. See your local Deere dealer for details.

	DB84	DB96
<b>Weight</b>	703 kg (1,550 lb.)	737 kg (1,625 lb.)
<b>Overall Width</b>	2133 mm (84 in.)	2438 mm (96 in.)
<b>Length</b>	800 mm (31.5 in.)	800 mm (31.5 in.)
<b>Blade Height</b>	610 mm (24 in.)	610 mm (24 in.)
<b>Blade Width (full angle)</b>	1882 mm (74.1 in.)	2151 mm (84.7 in.)
<b>Cutting Edge (reversible)</b>	16 x 153 mm (0.625 x 6 in.)	16 x 153 mm (0.625 x 6 in.)
<b>Degree of Angle</b>	30, right or left	30, right or left
<b>Degree of Tilt</b>	10, up or down	10, up or down
<b>Connection</b>		
Hydraulic	12.7-mm (0.5 in.) quick-connect couplers	12.7-mm (0.5 in.) quick-connect couplers
Electric	3 pin	3 pin
<b>Adjustable Skid Shoe</b>	Standard	Standard
<b>Vehicle Compatibility</b>	318G, 320G, and 324G SSLs; 317G and 325G CTLs	330G and 332G SSLs; 331G and 333G CTLs; and 204L, 244L, 304L, and 324L CWLs†

†CWLs require skid-steer-style Quik-Tatch™ coupler for operation.

**WORKSITE PRO™**

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

