

HYDRAULIC HAMMERS



JOHN DEERE

HH20C | HH40C | HH60C | HH80C



HYDRAULIC HAMMERS

HH20C | HH40C | HH60C | HH80C



Specifications

- These are the fastest hydraulic hammers on the market, with 30-percent fewer parts than either competitive or previous models, for simplified maintenance.
- Redesigned to provide two to three times more blows per minute (BPM) than previous models, for increased efficiency.
- Exclusive tool retention enables quick installation and removal using only one small screwdriver.
- Bits* available to power your productivity include:
 - Standard **moil point** suitable for breaking concrete or medium-hard, non-stratified rock.
 - Optional **chisel point** for most concrete flatwork, walls around rebar, or breaking into a precut line.
 - Optional **spade**, available in two sizes, for most concrete and all earthworks in soft, non-stratified rock.
 - Optional **compacting plate** for single-machine prep of dirt for concrete pads and fencing.
 - Optional **pyramid point**[†] used to break hard, reinforced concrete as well as sediment.
- Like all John Deere attachments, these hydraulic hammers are optimized to work with Deere skid steers (SSLs), compact track loaders (CTLs), and compact excavators (CEXs). They're also compatible with most competitive models. See your local Deere dealer for details.

*All bits are unique to this hydraulic hammer. All older bits will not be compatible.

[†]HH20C and HH40C only.

	HH20C	HH40C	HH60C	HH80C
Weight	150 kg (270 lb.)	190 kg (420 lb.)	228 kg (500 lb.)	315 kg (690 lb.)
Operating Pressure	90–150 bar (1,305–2,175 psi)	100–170 bar (1,450–2,465 psi)	80–130 bar (1,160–1,885 psi)	90–140 bar (1,305–2,030 lb.)
Pressure Relief	220 bar (3,190 psi)	220 bar (3,190 psi)	220 bar (3,190 psi)	220 bar (3,190 psi)
Impact Rate	800–3,000 BPM	700–2,600 BPM	600–1,800 BPM	500–1,700 BPM
Noise Level	118 dBA	119 dBA	122 dBA	124 dBA
Vehicle Compatibility	17G, 26G, 30G, and 35G CEXs [‡]	316GR, 318G, 320G, and 324G SSLs [‡] ; 317G and 325G CTLs; 26G, 30G, and 35G CEXs [‡]	312GR, 314G, 316GR, 318G, 320G, 324G, 330G, and 332G SSLs [‡] ; 317G, 325G, 331G, and 333G CTLs; 35G, 50G, and 60G CEXs [‡]	320G, 324G, 330G, and 332G SSLs [‡] ; 325G, 331G, and 333G CTLs; 50G and 60G CEXs [‡]

[‡]Mounting Bracket 9800 (17G), 9801 (26G and 35G), or 9802 (50G and 60G) required. All older mounting brackets will **not** interchange.

[‡]Front Protection Screen AT337084 (17G canopy), AT451135 (26G–60G cab), or AT435404 (26G–50G canopy) required.

[‡]Severe-Duty Door 5205 required.

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

