

POWER RAKES

PR60 | PR72B | PR84B | PR96B



JOHN DEERE



Power Rakes

PR60 | PR72B | PR84B | PR96B



Specifications

- Worksite Pro™ power rakes are perfect for landscape tasks such as seedbed preparation, rock raking, site development, and more.
- Adjustable end plates allow the power rake to do double duty as a box scraper, trapping and gathering stones for piling and pickup.
- Long-life carbide teeth on roller dig, lift, and pulverize dirt.
- Heavy-duty drive chain is housed in a sealed oil bath to reduce maintenance.
- Power rake roller assemblies can rotate 20 deg. from center in either direction, allowing material to be moved left or right (requires 12-volt kit).
- Forward and backward raking capability of the power rakes halves the time required for seedbed preparation.
- Like all Worksite Pro attachments, power rakes are optimized to work with John Deere skid steers and compact track loaders (CTLs), and are compatible with most competitive models. See your local Deere dealer for details.

	PR60	PR72B	PR84B	PR96B
Minimum Hydraulic Flow	49 L/min. (13 gpm)	49 L/min. (13 gpm)	60 L/min. (16 gpm)	60 L/min. (16 gpm)
Raking Width	1575 mm (62 in.)	1827 mm (72 in.)	2134 mm (84 in.)	2438 mm (90 in.)
Operating Width	1829 mm (72 in.)	2056 mm (81 in.)	2362 mm (93 in.)	2540 mm (100 in.)
Length	1499 mm (59 in.)	1625 mm (64 in.)	1625 mm (64 in.)	1930 mm (76 in.)
Height	787 mm (31 in.)	787 mm (31 in.)	812 mm (32 in.)	812 mm (32 in.)
Box End Plates	Front or rear	Front or rear	Front or rear	Front or rear
Tooth Roller Diameter	229 mm (9 in.)	229 mm (9 in.)	229 mm (9 in.)	229 mm (9 in.)
Weight	425 kg (938 lb.)	419 kg (925 lb.)	476 kg (1,050 lb.)	598 kg (1,320 lb.)
Angle Control (12-volt kit required)	12-volt actuation, 0–20-deg. rotation	12-volt actuation, 0–20-deg. rotation	12-volt actuation, 0–20-deg. rotation	12-volt actuation, 0–20-deg. rotation
Vehicle Compatibility	312GR, 314G, 316GR, and 318G Skid Steers	312GR, 314G, 316GR, 318E/G, 320E, 324E, 326E, 328E, 330G, and 332E/G Skid Steers; and 317G, 319E, and 323E CTLs	318E, 320E, 324E, 326E, 328E, 330G, and 332E/G Skid Steers; and 317G, 319E, 323E, 329E, 331G, and 333E/G CTLs	320E, 324E, 326E, 328E, 330G, and 332E/G Skid Steers; and 317G, 319E, 323E, 329E, 331G, and 333E/G CTLs

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

