

ROOT RAKES

RR72 | RR78 | RR84



JOHN DEERE



Root Rakes

RR72 | RR78 | RR84



Specifications

- Designed specifically for land clearing, ground leveling, and moving materials away from buildings and obstructions more quickly and economically than dozer blades.
- Handily gather rocks and debris while allowing soil to sift through, for minimal site and landscape disturbance.
- Alloy-steel construction, replaceable pin-on teeth, and zinc-plated greaseable pivot pins with protected zerks and hardened-steel bushings ruggedly resist impact.
- Attachment height and width help shield the front of the machine against large piles of brush or jagged scrap.
- Weld-on “D” ring enables the tackling of a wide variety of jobsite tasks.
- Like all Worksite Pro attachments, these root rakes are optimized to work with John Deere G- and E-Series Skid Steers and Compact Track Loaders (CTLs), and K-Series Compact Wheel Loaders. They’re also compatible with many competitive models. See your local Deere dealer for details.

	RR72	RR78	RR84
Overall Width	1830 mm (72 in.)	1980 mm (78 in.)	2135 mm (84 in.)
Overall Height	990 mm (38.9 in.)	990 mm (38.9 in.)	990 mm (38.9 in.)
Overall Length	780 mm (30.8 in.)	780 mm (30.8 in.)	780 mm (30.8 in.)
Grapple			
Width	1780 mm (70 in.)	1780 mm (70 in.)	1780 mm (70 in.)
Opening	1295 mm (51 in.)	1295 mm (51 in.)	1295 mm (51 in.)
Tooth Position	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)
Tine Spacing	240 mm (9.5 in.)	255 mm (10 in.)	215 mm (8.5 in.)
Weight	497 kg (1,095 lb.)	522 kg (1,150 lb.)	553 kg (1,220 lb.)
Cylinder			
Bore	65 mm (2.5 in.)	65 mm (2.5 in.)	65 mm (2.5 in.)
Stroke	230 mm (9 in.)	230 mm (9 in.)	230 mm (9 in.)
Rod Diameter	40 mm (1.5 in.)	40 mm (1.5 in.)	40 mm (1.5 in.)
Vehicle Compatibility	318G, 320E, 324E, and 330G Skid Steers; 317G and 323E CTLs; and 204K, 244K, 304K, 324K, and 344K Compact Wheel Loaders	320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; and 204K, 244K, 304K, 324K, and 344K Compact Wheel Loaders	330G and 332G Skid Steers; 323E, 331G, and 333G CTLs; and 204K, 244K, 304K, 324K, and 344K Compact Wheel Loaders

WORKSITE PRO

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

