

SNOW/UTILITY V-BLADES



JOHN DEERE

BV6 | BV8 | BV9



SNOW/UTILITY V-BLADES

BV6 | BV8 | BV9



Specifications

- Worksite Pro™ snow/utility V-blades provide multifunction versatility for snow removal and light dirt work.
- Blades angle hydraulically to four positions: **straight** for larger cuts, **V-configuration** for pushing through hard pack, **scoop** (both sides inward) for easy snow stacking, and **30 deg. right or left**.
- Adjustable skid shoes for vertical blade productivity are standard.
- Steel cutting edge is standard. Available rubber cutting edge helps prevent damage to decorative surfaces.
- Trip springs help protect the vehicle from sudden impacts with concealed obstacles and can be locked out for light grading and dirt work.
- Electrohydraulic (EH) valve for independent blade function is adjustable from the cab.*
- Top blade extension for extra carrying capacity is available.
- Like all Worksite Pro attachments, these V-blades are optimized to work with John Deere G-Series Skid Steer Loaders (SSLs) and Compact Track Loaders (CTLs), and L-Series Compact Wheel Loaders (CWLs). They're also compatible with many competitive models. See your local Deere dealer with questions or for details on attachment-control kits if not ordered as a factory-installed option.

*SSLs, CTLs, and CWLs require 1/2-in. auxiliary couplers and a 14-pin electrical connector for blade operation.

	BV6	BV8	BV9
Width			
Straight	1880 mm (74 in.)	2489 mm (98 in.)	2794 mm (110 in.)
V-Configuration	1638 mm (64.5 in.)	2172 mm (85.5 in.)	2438 mm (96 in.)
Scoop	1600 mm (63 in.)	2134 mm (84 in.)	2413 mm (95 in.)
30-deg. Angle	1626 mm (64 in.)	2159 mm (85 in.)	2416 mm (95 in.)
Height	711 mm (28 in.)	711 mm (28 in.)	711 mm (28 in.)
Oscillation	± 10 deg.	± 10 deg.	± 10 deg.
Operating Weight	441 kg (972 lb.)	480 kg (1,058 lb.)	500 kg (1,102 lb.)
Vehicle Compatibility	316GR and 318G	318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 33G CTLs; 204L, 244K-II, 304L, 324K, and 344L CWLs	318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 33G CTLs; 204L, 244K-II, 304L, 324K, and 344L CWLs

WORKSITE PRO

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

