

ANGLE BROOMS



JOHN DEERE

BA72C | BA84C | BA96C



ANGLE BROOMS

BA72C | BA84C | BA96C



Specifications

- Angle brooms feature an 810-mm (32 in.)-diameter brush with standard 50/50 poly-wire segments. Optional all-polypropylene brush segments are available.
- Brush-core removal for bristle replacement is quick and easy, with no tools required. Motor and bearing separate from the brush core without having to disconnect any hydraulic hoses, eliminating the risk of oil spills or contamination.
- Heavy-duty, high-torque, bidirectional motor is coupled to the brush core through a 63.5-mm (2.5 in.) hex hub. Motor and bearing are protected within the broom-frame structure.
- Hydraulic-angling range of 30 deg. to right or left is standard.
- Foldaway storage stands help the brush maintain its round shape when not in use.
- Optional hood extension provides 180-deg. brush coverage; a rubber deflector prevents snow from blowing back onto the machine when winter strikes.
- Optional 114-L (30 gal.) roof-mounted water-tank kit is available for applications that require dust suppression.
- Like all John Deere attachments, these angle brooms are optimized to work with Deere skid steers (SSLs) and compact track loaders (CTLs). They're also compatible with most competitive models. See your local Deere dealer for details.

	BA72C	BA84C	BA96C
Weight	410 kg (910 lb.)	440 kg (960 lb.)	460 kg (1,010 lb.)
Sweeping Angle	±30 deg.	±30 deg.	±30 deg.
Overall Length			
Straight	1740 mm (69 in.)	1740 mm (69 in.)	1740 mm (69 in.)
Angled at 30 deg.	2030 mm (80 in.)	2110 mm (83 in.)	2180 mm (86 in.)
Overall Width			
Straight	2330 mm (92 in.)	2640 mm (104 in.)	2940 mm (116 in.)
Angled at 30 deg.	2230 mm (88 in.)	2490 mm (98 in.)	2760 mm (109 in.)
Sweeping Width			
Straight	1830 mm (72 in.)	2130 mm (84 in.)	2440 mm (96 in.)
Angled at 30 deg.	1580 mm (62 in.)	1850 mm (73 in.)	2110 mm (83 in.)
Overall Height	1010 mm (40 in.)	1010 mm (40 in.)	1010 mm (40 in.)
Brush Diameter	810 mm (32 in.)	810 mm (32 in.)	810 mm (32 in.)
Core Diameter	250 mm (10 in.)	250 mm (10 in.)	250 mm (10 in.)
Number of Wafers	35	41	47
Hydraulic Flow			
Minimum	57 l/min. (15 gpm)	57 l/min. (15 gpm)	57 l/min. (15 gpm)
Maximum	95 l/min. (25 gpm)	95 l/min. (25 gpm)	95 l/min. (25 gpm)
Motor Pressure Relief Setting	17 000 kPa (2,500 psi)	17 000 kPa (2,500 psi)	17 000 kPa (2,500 psi)
Brush Coverage	180 deg.	180 deg.	180 deg.
Roof-Mounted Water Tank			
Water-Tank Capacity	114 L (30 gal.)	114 L (30 gal.)	114 L (30 gal.)
Pump Flow	6.8 l/min. (1.8 gpm)	6.8 l/min. (1.8 gpm)	6.8 l/min. (1.8 gpm)
Vehicle Compatibility	312GR, 314G, 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs	330G and 332G SSLs; 331G and 333G CTLs

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

