

# HIGH-TORQUE STUMP SHREDDER



JOHN DEERE

SS30





# HIGH-TORQUE STUMP SHREDDER

SS30

## Specifications

- Remove stumps from 203 to 711 mm (8 to 28 in.) in diameter in a single pass. Easily remove larger stumps with multiple bores.
- Hardened pilot cone draws auger into the stump while 19-mm (0.75 in.)-thick AR500 steel blades efficiently make the cut.
- Low-speed, high-torque auger planetary drive shreds material more safely and without the dangerous flying debris of conventional stump grinders.
- Bore 508 mm (20 in.) into the ground to remove feeder roots.
- Even with slower operating speeds, stump removal is faster than with conventional stump grinders. Site cleanup is easy thanks to the small, contained chip pile.
- No carbide tools to replace lowers operating costs, and maintenance required only every 1,000 stumps maximizes uptime.
- Like all Worksite Pro™ attachments, this stump shredder is optimized to work with John Deere skid steers and compact track loaders (CTLs). It's also compatible with most competitive models. See your local Deere dealer for details.



SS30	
Weight	590 kg (1,300 lb.)
Length	1670 mm (66 in.)
Width	1160 mm (46 in.)
Height	770 mm (30 in.)
Hydraulic Flow	
Minimum	76 L/min. (20 gpm)
Maximum	170 L/min. (45 gpm)
Maximum Operating Pressure	28 000 kPa (4,000 psi)
Maximum Output Torque	40 670 Nm (30,000 lb.-ft.)
Output Speed	
76 L/min. (20 gpm)	7.0 rpm
95 L/min. (25 gpm)	9.0 rpm
114 L/min. (30 gpm)	11.0 rpm
132 L/min. (35 gpm)	13.0 rpm
151 L/min. (40 gpm)	14.5 rpm
170 L/min. (45 gpm)	16.5 rpm
Maximum Auger Bit Diameter	760 mm (30 in.)
Overall Auger Bit Length	800 mm (32 in.)
Connection	
Hydraulic	12.7-mm (0.5 in.) quick-connect couplers with 9.525-mm (0.375 in.) case-drain coupler
Electrical	None
Vehicle Compatibility	320G, 324G, 330G, and 332G Skid Steers; 325G, 331G and 333G CTLs

**WORKSITE PRO**

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

